



The industry's first wireless tabletop conference phone. MAX Wireless provides the flexibility to hold a conference call when and where it's most convenient – with no cables in the way.

MAX Wireless is a perfect fit for offices and small conference rooms, delivering outstanding audio clarity.

Superior Audio Performance

- + Distributed Echo Cancellation[®] effectively eliminates echo
- + Noise cancellation removes background noises from fans or HVAC systems
- + True full-duplex performance allows users to speak and listen at the same time without audio cutting in and out
- + Automatic level controls keep participants' audio balanced and consistent
- + First-mic priority eliminates hollow "tunnel" sound by activating only the microphone closest to the person speaking
- + Three microphones provide 360° audio pickup
- + ClearEffect™ provides natural, full-sounding audio without requiring wideband on both ends

Wireless Capabilities

- + Turn any room into a conference room, even without a phone line
- + Wireless signal range allows use in multiple rooms without moving the base unit
- + Wireless design provides a clean look with no wires on tables or floors
- + 12 hours of talk time allows for lengthy conferences without recharging; 36 hours of standby time reduces recharging frequency; automatic power-save mode conserves battery life
- + Dual-function power supply/charger enables conferencing while charging
- + Digital spread-spectrum technology with 64-bit encryption ensures secure conferencing
- + Audible warnings signal when phone is out of range or needs charging
- + Phone paging button allows easy identification of phone's location

Ease of Use & Control

- + Simple plug-and-play functionality makes installation and configuration a snap
- + Field-upgradeable for easy access to latest features
- + Selectable ring tones
- + Features user-friendly, telephone-style controls
- + Speed dial stores 10 frequently dialed numbers
- + Recording output on base unit connects to a recording device to capture both sides of the conversation
- + Both phones can be operated using the dial pad of either phone - dialing, mute, volume controls, etc



VENUES


Boardrooms

Small Conference Rooms

Huddle Rooms

Home Office

Any Room Without Phone Lines



MAX Wireless is a single conference phone that connects wirelessly to a base unit for use in any small room.

PRODUCT SPECIFICATIONS

Echo Cancellation

- Tail time: 60 ms x 3

Noise Cancellation

- Dynamic noise cancellation

Telephone Connection

- Analog PBX or PSTN line
- RJ-11C, -12 dBm nominal

Radio

- Standard DECT/DECT 6.0 (NA, Canada, LATAM)
- WDCT (EMEA, APAC)
- ETSI EN 300 175 1-9

Keypad

- Alphanumeric standard keypad

Loudspeaker

- Volume: 90 dBspl A weighted @ 1 ft
- Bandwidth: 200 Hz–3.3 kHz

Record Output

- Connector: 2.5 mm mono audio jack
- Impedance: <1000 ohms
- Bandwidth: 200 Hz–3.3 kHz
- Dynamic range: 60 dB
- THD <.01%

Certifications

- FCC part 15/ICES-003 Class A
- FCC part 15 Subpart C/RSS-210
- FCC part 68/IC CS-03
- CE
- UL Certified

Power

Phone Unit:

- Custom battery pack with nickel metal hydride batteries, 7.2 V 2200 mAh
- 12 hours continuous talk time (typical)
- 36 hours standby

Base Unit:

- Auto-adjusting power module;
- 100-240 VAC; 50/60Hz

- DECT: 300 ft to 400 ft (91-121 m)
- EU WDCT unit: 50 ft (15 m)

Note: these ranges depend on environmental factors and may vary. The EU unit has a shorter range due to regulatory restrictions on power output in the 2.4 GHz frequency band in the EU.

Environmental

- Operating temperature: 32–118° F (0–48° C)
- Storage temperature: 41–158° F (5–70° C)
- Operating humidity: 15 to 80%
- Storage humidity: 10 to 90%

Dimensions (W x D x H)

- Phone unit: 10.5" x 10.5" x 3"
- (26.7 cm x 26.7 cm x 7.6 cm)
- Base unit: 4.25" x 5.5" x 2.5"
- (10.8 cm x 14 cm x 6.4 cm)

Weight

- Phone unit: 2.7 lb (1.2 kg)
- Base unit: .6 lb (0.27 kg)
- Shipping: -MAX Wireless: 10 lb (4.5 kg)

MAX Wireless Includes

- Wireless phone unit (2)
- Base unit (1)
- Battery pack (2)
- Power supply/charger (2)
- Power supply retainer (2)
- Telephone cable
- Documentation CD
- Quick start guide

Part Numbers

- 910-158-600 (NA, Canada, LATAM)
- 910-158-276 (EMEA)
- 910-158-406 (Singapore/HK)

SALES AND INQUIRIES

North America

Tel: +1 801.975.7200
TollFree: +1 800.945.7730
TechSales: +1 800.705.2103

Fax: +1 801.303.5711
sales@clearone.com

Europe

Tel: +1.800.945.7730
global@clearone.com

Middle East

Tel: +1.800.945.7730
global@clearone.com

Asia Pacific

Tel: +1.800.945.7730
global@clearone.com

Other Regions

Tel: +1.800.945.7730
global@clearone.com