



CONVERGE Pro 2 is the industry's most advanced professional audio DSP platform for conferencing and sound reinforcement applications. It outperforms in any size room, audio environment, and application.

The 48V model mixer has 4 inputs with AEC, 8 outputs, built-in VoIP/Skype for Business interface, USB audio; GPIO, RS232, IP control interfaces; and P-Link and C-Link expansion buses.

CONVERGE Pro 2 is optimized to work with the new Beamforming Mic Array 2 and DIALOG® 20 2-Channel Wireless Microphone System through its native connection.

### Powerful Architecture

- + 4 Mic/Line inputs with AEC
- + Built-in VoIP: 5 lines
- + Built-in Skype for Business Client
- + Separate ports for VoIP/Skype for Business and Ethernet
- + Built-in USB for PC-based conferencing
- + Reduced footprint and power consumption

### Scalable Connectivity

- + Standalone and daisy-chained system
- + Stack up units up to 144 Mic/Line inputs
- + Expansion bus "C-Link" with 64 channels
- + "P-Link" bus to connect peripheral devices

### Configuration & Management

- + New CONSOLE® software
- + Auto-discovery of devices
- + MatrixView™ for entire system
- + FlowView™ for visualized audio signal paths
- + System monitoring and troubleshooting

### Audio Signal Processing

- + Next-gen Acoustic Echo Cancellation processing
- + Distributed Echo Cancellation® on every mic input
- + Noise Cancellation with Adaptive-Ambience
- + Acoustic Intelligence with faster convergence
- + DARE™ feedback elimination
- + Advanced microphone gating

### Applications

- + VoIP conferencing
- + PC-based conferencing & Unified Communications
- + Microsoft Skype for Business audio conferencing

### Flexible Control Options

- + Dialer app for Windows, Mac, iOS, Android
- + Touch Panel Controller with tabletop and wall mount options
- + 3<sup>rd</sup>-party control modules



### APPLICATIONS

Boardrooms

Conference Rooms

Huddle Rooms

Training Rooms

Lecture Halls

Courtrooms

Auditoriums

Telemedicine Facilities



## PRODUCT SPECIFICATIONS

Unless otherwise specified, all measurements are performed with a 20Hz to 22kHz BW (no-weighting).

### MIC/LINE INPUTS & OUTPUTS

**Inputs:** Balanced audio inputs, 3.81mm Orange color Phoenix/Euroblock type male header, Push-on mini-terminal block

**Outputs:** Balanced audio outputs, 3.81mm Black color Phoenix/Euroblock type male header, Push-on mini-terminal block

**Frequency Response:** 20Hz – 22kHz @ +4dBu, +/- 0.5dBu

**EIN (Equivalent Input Noise):** 20kHz BW, max gain,  $R_s = 150\Omega$ , -126dBu

**THD + N (Total Harmonic Distortion + Noise):**

- 20Hz – 22kHz @ +4dBu, line level, 0.006%
- 20Hz – 22kHz @ -56dBu, mic level, <0.04%

**Dynamic Range:** 20Hz – 20kHz @ 0dB, >105dB

**Crosstalk (Mic/Line):** Channel to Channel, stimulus at 20dBu to receptor at -56dBu, 1kHz, < -98dB

**Input Impedance:** Balanced (line to ground), 2.2k $\Omega$ , 1%

**Nominal Input Level:** Adjustable -56dB to 0dB, 7dB step coarse gain

**Maximum Input Level:** -65dBu to 20dBu

**Phantom Power:** 48V, Impedance 6.81k $\Omega$

**Output Impedance:** Balanced (line to ground), 95 $\Omega$ , 1%

**Output Level:** 0dBu (Nominal), 20dBu (Max), -40dBu (Selectable)

### USB AUDIO

**Port Type:** USB-B connector

**Audio:** Digital Audio, 2 x 2 bidirectional channels

**Sample Rate:** 48kHz

**Sample Bit Depth:** 24-Bit

**Compatible:**

- USB 2.0
- USB 3.0

### VOIP

**Port Type:**

RJ-45, 10/100Mbps Ethernet Network, Auto Negotiation

**Audio:**

5 Lines

Number of Lines	Maximum Number of Calls per Line
1	5
2	5
3	4
4	3
5	2

**Codec:**

- G.711 uLaw
- G.711 ALaw
- G.722

**Skype for Business (S4B):**

- Microsoft Skype for Business support (1 client)
- Choose either regular VoIP or S4B through configuration

### ETHERNET

**Port Type:**

RJ-45, 10/100Mbps Ethernet Network, Auto Negotiation

**IP address:** IPv4 (IPv6 upgradeable through future s/w, f/w upgrade)

### AMPLIFIER OUTPUT

**Speaker Output Port:** Dual binding posts

**Audio:** 2 Channels

**Output Power:** 10W Max, 8 $\Omega$  load

**Frequency Response:** 20Hz – 22kHz @ +10dBu, +/- 0.5dBu

**THD + N:** 20Hz – 22kHz @ +10dBu, 1W, <0.3%

**Dynamic Range:** 20Hz – 22kHz @ 20dB, >102dB, with 20kHz digital low pass filter

**Crosstalk:** Channel to Channel, stimulus at 20dBu, 10W output to receptor 8 $\Omega$  load, 20Hz – 22kHz, < -70dB

### C-LINK EXPANSION BUS

**Ports Type:** RJ-45 (Cat5e or Cat6)

**C-Link In & Out:** Proprietary Expansion Bus

**Audio:** 64 Expansion channels

**Cable:** Solid core, factory terminated Cat 5e or 6 cable

**Distance:** Up to 150' (45M)

### P-LINK PERIPHERAL BUS

**Ports Type:** RJ-45 (Cat5e or Cat6)

**P-Link In & Out:** Proprietary Peripheral Bus

**PoE In:**

- P-Link In Port
- PoE 802.3af Mode B, Midspan
- Power on "spare pairs" 4,5 and 7,8
- Input voltage range: 48V to 56V

**Audio:** Up to 3 Beamforming Microphone Array 2 units + up to 3 DIALOG 20 Wireless Receiver units + Up to 3 USB Expander units + Up to 3 GPIO Expander units

**Cable:** Solid core, factory terminated Cat 5e or 6 cable

**Distance:** Up to 200' (60M)

### RS232

**Port Type:** DB9 Female

**Settings:** 9600/19200/38400/57600/115200 Baud;

Serial Echo; Flow Control

**Support:** Serial commands

### GPIO

**Port Type:**

5.08mm Green color Phoenix/Euroblock type male header

**Support:** Control, Status, Variable Voltage Control

**Power Pin:** 5V DC @ 350mA Power Source

**Pin 1 to 4:**

- Open Collector Outputs: 40VDC @ 250mA
- Active Outputs (Source/Sink): 5VDC @ 25mA
- Logic Inputs: 40.2k $\Omega$  pull up
- Variable Voltage Control Inputs: 5VDC max

**Ground Pin:** GND

### USB CONTROL

**Port Type:** USB-B connector

**Location:** Front Panel

**Compatible:**

- USB 2.0
- USB 3.0

### LEDs

**Location:** Front Panel

**Status LED:**

- Off: Unit still initializing
- Blue - Fast Blinking: Stack Syncing in progress
- Blue - Slow Blinking: Unit not configured
- Blue - Solid: Configured unit
- Red - Fast Blinking: Stack Sync error

**Locate LED:**

Blue - Blinking: Unit "Locate" command received

**Power LED:**

Blue - Solid: Unit is powered on

### TOUCH SENSOR

**Sensor Type:** Capacitive Touch Button

**Location:** Front Panel

### POWER & THERMAL

**Port Type:** AC Inlet

**Mains Voltage:** 100-240V AC, 50/60Hz

**Power Consumption:** 50 Watts Typical

**Thermal:** 170 BTU/Hr Typical

**Operating Temperature:** 14°F (-10°C) to 104°F (40°C) Ambient Temperature

### DIMENSION & WEIGHT

**RU size:** 1 RU

**Width x Depth x Height:**

- Without rack-ears: 17"W x 10.73"D x 1.72"H (43.2cmW x 27.3cmD x 4.4cmH)
- With rack-ears: 19"W x 10.73"D x 1.72"H (48.3cmW x 27.3cmD x 4.4cmH)

**Unit Weight:** 9.3 lbs (4.2 kg) (Approximately)

**Shipping Weight:** 13.8 lbs (6.3 kg) (Approximately)

### PACKAGE

**Power Cord:** 6' (1.8M), Grounded, Qty 1

**Input Connectors:**

Terminal Block Connector, 3 Position (Orange), Qty 12

**Output Connectors:**

Terminal Block Connector, 3 Position (Black), Qty 8

**GPIO Connector:**

Terminal Block Connector, 6 Position (Green), Qty 1

**C-Link Cable:**

RJ-45 To RJ-45 Cable, 18" (45.7cm), Qty 1

**VoIP Cable:** RJ-45 To RJ-45, 7' (2M), Qty 1

**USB Cable:** USB Type A to Type B, 6' (1.8M), Qty 1

**Rack Ears:** Pre-installed, Qty 2

**Screw/Washer Kit:** Rack Decor, Qty 4

### PART NUMBERS

Part Number	Product
910-3200-001	CONVERGE Pro 2 128
910-3200-001-D	CONVERGE Pro 2 128D
910-3200-002	CONVERGE Pro 2 128T
910-3200-002-D	CONVERGE Pro 2 128TD
910-3200-003	CONVERGE Pro 2 128V
910-3200-003-D	CONVERGE Pro 2 128VD
910-3200-005	CONVERGE Pro 2 48T
<b>910-3200-006</b>	<b>CONVERGE Pro 2 48V</b>
910-3200-004	CONVERGE Pro 2 120
910-3200-007	CONVERGE Pro 2 012
910-3200-101	CONVERGE Pro 2 128SR
910-3200-101-D	CONVERGE Pro 2 128SRD

## SALES AND INQUIRIES

### Headquarters

5225 Wiley Post Way,  
Suite 500  
Salt Lake City, UT 84116

### US & Canada

Tel: 801.975.7200  
TollFree: 800.945.7730  
Fax: 801.303.5711

### International

Tel: +1.801.975.7200  
global@clearone.com

### Sales

Tel: 801.975.7200  
sales@clearone.com

### TechSupport

Tel: 801.974.3760  
tech.support@clearone.com