



Group USB speakerphone, powered by ClearOne's market leading HDConference™ audio, enhances your web conferencing, unified communications and video conferencing experience in your personal workspace, huddle rooms, small and medium-size conference rooms with crystal-clear audio for business class performance.

HDConference Audio

- + Distributed Echo Cancellation® and noise cancellation along with full-duplex performance and automatic level controls guarantee your conference calls to be natural with unmatched audio clarity free of any distractions

Full-duplex Speakerphone Capabilities on PCs or Laptops

- + Connect the CHAT 150 or the CHATAttach 150 to laptops & PCs via USB for hands-free audio

Acoustic Intelligence

- + First-mic priority intelligently activates only the microphone closest to the person speaking, preventing the amplification of ambient noise and room reflections

Expandable Design

- + Daisy-chainable design can expand up to two complete speakerphones to cover medium or large rooms. Full speakerphone expandability allows both mic and speaker to cover the entire room along with flexibility of control using any speakerphone



VENUES

Conference Rooms/Boardrooms

Internet Telephony

VoIP Softphones

Web Conferencing




CHAT 150



USB 2.0
Connection Cable
Part# 830-156-200



Quick Start Guide
Part# 800-156-202



Two CHAT 150 Units
Part# 910-156-200



USB 2.0
Connection Cable
Part# 830-156-200




CHATAttach
Cable
Part# 830-156-010L




CHATAttach
Power Supply
Part# 551-156-200



CHATAttach
Quick Start Guide
Part# 800-156-225



CHAT 150



CHATAttach 150

PRODUCT SPECIFICATIONS

System Requirements:

Microsoft Windows 7, 8, 10
(For any firmware upgrades, use Win7)

Mac OS

Connections:

USB:
Version 2.0 Compatible
Type: Mini-B Female

Keyed Connector:
Keyed RJ-45 (8-conductor)

Line Input/Output via VC Breakout Box (BOB):

Frequency Response:
20Hz - 20 kHz +/- 1 dB
Maximum Level: +6 dBu
Input Impedance: 10 kΩ
Output Impedance: 50 Ω

Controls:

Volume Up
Volume Down
Microphone Mute

Audio:

Speaker:
Bandwidth: 190 Hz - 20 kHz
Max Output Level: 85 dB SPL @ 1 foot (0.30 meter)

Microphone:
Bandwidth: 50 Hz - 7.75 kHz

Environmental:

Operating Temperature:
41 - 104° F (5 - 40° C)

Processing:

Full Duplex

Distributed Echo Cancellation (D.E.C.)®

Noise Cancellation (NC)

Automatic Level Control (ALC)

Line Echo Cancellation (LEC) - Selectable

First-Mic Priority

Power:

USB:
5 VDC @ 500 mA Maximum

External:
Input: 100 - 240 VAC
Output: 9 VDC @ 560 mA
Tip: Power
Ring: Ground

Mechanical:

Dimensions (W x D x H):
7.4" x 7.4" x 1.8" (18.8 cm x 18.8 cm x 4.6 cm)

Weight:
1.17 lbs (0.53 kg)

Compliance:

RoHS

REACH

FCC Class A Part 15

ICES-003

CE Listed

UL Listed

Model Numbers:

910-156-200 CHAT 150 USB:
Single CHAT 150 and Connecting Cable

910-156-200-00 CHATAttach 150:
Two (2) CHAT 150 Devices, Connecting Cables and Power Supply

910-156-222 CHAT 150 Avaya:
CHAT 150 and Connecting Cable to Avaya Enterprise Phone

910-156-220 CHAT 150 Cisco:
CHAT 150 and Connecting Cable to Cisco Enterprise Phone

910-156-230 CHAT 150 VC:
CHAT 150 and Cable to Video Conference System

Accessory Part Numbers:

860-156-230L CHAT 150 VC Accessory Kit:
Includes Video Conferencing Breakout Box, Power Adapter, International Power Clips, RCA Connection Cable, 25' Link Cable

860-156-222L CHAT 150 Avaya Accessory Kit:
Includes Breakout Box for 2410, 2420, 4610 and 4621 Telephone Handsets, Power Adpater, International Power Clips, RJ-9/RJ-9 Telephone Cable, 25' Link Cable

860-156-220L CHAT 150 Cisco Accessory Kit:
Includes Breakout Box for 7940, 7960, and 7970 Telephones, Power Adapter, International Power Clips, RJ-9/RJ-9 Telephone Cable, 25' Link Cable

910-156-225 CHATAttach Expansion Kit:
Includes Cables, Power Supply and Quick Start Guide to Update Two (2) CHAT 150 Devices to CHATAttach

SALES AND INQUIRIES

Headquarters

5225 Wiley Post Way,
Suite 500
Salt Lake City, UT 84116

US & Canada

Tel: 801.975.7200
TollFree: 800.945.7730
Fax: 801.303.5711

International

Tel: +1.801.975.7200
global@clearone.com

Sales

Tel: 801.975.7200
sales@clearone.com

TechSales

Tel: 801.974.3760
techsales@clearone.com

TechSupport

Tel: 801.974.3760
tech.support@clearone.com