

# LS5WT WALL SPEAKERS

Designed to provide high-quality audio in small and large meeting spaces.



- > Passive, 2-way wall-mount, coaxial 4-inch speaker.
- > Adjustable wall-mount speaker with included wall-mount bracket.

## Specifications

<b>Part Number</b> .....	• 910-151-002-01 LS5WT WALL SPEAKERS
<b>Speaker Type</b> .....	• 2-way, Wall Mount Speaker
<b>Frequency Range</b> .....	• 80 Hz - 19 kHz
<b>Power Handling</b> .....	• 30 Watts RMS, 80 Watts Peak
<b>Nominal Sensitivity</b> .....	• 90 dB SPL, 1 W @ 1 m
<b>Nominal Coverage Angle</b> .....	• 110 ° Conical Coverage
<b>Nominal Impedance</b> .....	• 80 Ohms
<b>Transformer Taps</b> .....	• 70 V - 30 W, 15 W, 7.5 W, 3.8 W, 1.9 W • 100 V - Null, 30 W, 15 W, 7.5 W, 3.8 W Woofer diameter: 6.5 in (165 mm)
<b>Woofer</b> .....	• 05 " (127 mm) poly-propylene cone with moisture resistant rubber coating
<b>Tweeter</b> .....	• 0.5 " (12.7 mm) Mylar Tweeter
<b>Termination</b> .....	• Two (2) Input Termination Screws (Red = Positive Post, Silver = Negative Post)
<b>Dimensions</b> .....	• 11.26 " x 8.27 " x 7.48 " (286 mm(H) x 210 mm(W) x 190 mm(D))
<b>Net Weight (each)</b> .....	• 5 lbs (2.27 Kg)

## SALES AND INQUIRIES

### Headquarters

5225 Wiley Post Way  
Suite 500  
Salt Lake City, UT 84116

### US & Canada

Tel: +1.801.975.7200

### International

Tel: +1.801.975.7200

### Sales

Tel: +1.801.975.7200  
sales@clearone.com

### Tech Support

Tel: +1.801.974.3760  
videotechsupport@clearone.com