

# LS6CT CEILING SPEAKERS

Designed to provide high-quality audio in small and large meeting spaces.



- > 2-way, ceiling speaker with metal back can.
- > Overload Full Protection: Full range power limiter with the 8 ohm direct input only, protecting the tweeter, woofer and crossover.

### Specifications

<b>Part Number</b> .....	• 910-151-001-01 LS6CT CEILING SPEAKERS
<b>Speaker Type</b> .....	• 2-way, ceiling speaker with metal back can
<b>Frequency Range</b> .....	• 65 Hz - 20 kHz
<b>Power Handling</b> .....	• 60 Watts RMS, 120 Watts Peak
<b>Nominal Sensitivity</b> .....	• 88 dB, 1 W @ 1 m
<b>Nominal Impedance</b> .....	• 8 Ohms
<b>Transformer Taps</b> .....	• 70 V - 30 W, 15 W, 7.5 W, 3.8 W, 1.9 W • 100 V - Null, 30 W, 15 W, 7.5 W, 3.8 W Woofer diameter: 6.5 in (165 mm)
<b>Woofer</b> .....	• 6.5 " (165 mm) poly-propylene cone with moisture resistant coating
<b>Tweeter</b> .....	• ¾ " (19 mm) silk dome
<b>Overload Protection</b> .....	• Full range power limiter with the 8 ohm direct input only, protecting the tweeter,woofer and crossover
<b>Dimensions</b> .....	• 10.24 " (260 mm) diameter, 7.40 " (188 mm) deep
<b>Net Weight (each)</b> .....	• 3.5 Kg (7.71 lbs)

### SALES AND INQUIRIES

#### Headquarters

5225 Wiley Post Way  
Suite 500  
Salt Lake City, UT 84116

#### US & Canada

Tel: +1.801.975.7200

#### International

Tel: +1.801.975.7200

#### Sales

Tel: +1.801.975.7200  
sales@clearone.com

#### Tech Support

Tel: +1.801.974.3760  
audiotechsupport@clearone.com