

# UNITE® 260N Pro Camera



A professional 4K Ultra HD camera with NDI|HX2, designed to meet the requirements of NDI workflows. Experience real time camera control, switching, and IP streaming, enabling dynamic broadcast-style video. Expand your reach and effortlessly engage larger audiences, eliminating the need for complex and costly setups.

- > Motorized pan-tilt-zoom (PTZ), 20x optical zoom, plus 16x digital zoom provides the capability to capture all participants in the room.
- > AI-based auto framing mode always keeps the entire group perfectly in view.
- > Seamlessly re-acquire and track individuals even after they leave the frame. Eliminate tracking loss and refocusing delays, thanks to advanced Re-Identification technology.
- > Capture meetings and lecturers directly to USB for easy sharing and review with Local MP4 Recording.
- > A high SNR CMOS sensor combined with 2D and 3D noise reduction algorithms provide a super clean image, even under low light conditions.
- > Streams AV over IP using H.264 and H.265 video compression.
- > Compatible with popular applications such as Microsoft® Teams, Zoom™, WebEx™, Google® Meet™, and more.
- > Control the camera's functions via USB, Ethernet, RS-485, and RS-232.
- > Can be powered by PoE (48V DC), or 12V DC power supply.

### Supports NDI|HX2

Benefit from the efficiency of NDI|HX2, featuring built-in encoding capabilities for seamless integration with your connected devices.



### AI-based Smart Face Tracking

AI-based smart face tracking keeps the selected presenter in the frame as they move around the room.

#### APPLICATIONS

- Video Conferencing
- Hybrid Learning
- Rental and Staging
- Weddings
- Surveillance

#### WORKSPACES

- Large Conference Rooms
- Concert Venues
- Classrooms
- Houses of Worship

## Elevate Your Collaboration

# UNITE® 260N Pro Camera

## Different Tracking Modes



### Customizable Zone Tracking

Define focus areas within the room for optimal capture. Ideal for classrooms, conferences, stages, and more.

### Auto Framing

Detects a participant or a group of participants and automatically frames the image. Always keeps the entire group perfectly in view.



### AI-based Smart Face Tracking

In this mode, the camera will keep a selected person in focus and perfectly framed as that person walks around the room.

# UNITE® 260N Pro Camera

- CAMERA** .....
- Video System:
    - 2160p30
    - 2160p25
    - 1080P30
    - 1080P25
  - Sensor: 1/1.8 inch, CMOS
  - Effective Pixels: 8.51 Million
  - Scanning Mode: Progressive
  - Lens: 20x maximum zoom, Focal length: 4.4 mm – 88.5 mm, F1.8 – F2.6
  - Minimal Illumination: 0.5 lux @ (f2.0, Agc ON)
  - Shutter: 1/30 s – 1/10000 s
  - White Balance: Automatic, indoor, outdoor, one-button, manual, specified color
  - Backlight Compensation: Supported
  - Digital Noise Reduction: 2D & 3D Digital Noise Reduction
  - Signal to Noise Ratio ≥55 dB
  - Horizontal Angle of View: 60.7° – 3.36°
  - Vertical Angle of View: 34.1° – 1.89°
  - Horizontal Rotation Range: ±170°
  - Vertical Rotation Range: -30° – +90°
  - Pan Speed Range: 1.7° – 100°/S
  - Tilt Speed Range: 1.7° – 69.9°/S
  - H & V FLIP: Supported
  - Image Freezing: Supported
  - Number of Presets: 255
  - Preset Accuracy: 0.1°
- INPUT/OUTPUT INTERFACE** .....
- USB Interface: USB 3.0, Type C socket
  - HD Output: 1 channel, HDMI1.4b
  - Network Interface: 1 x RJ45: 10 M/100 M Adaptive Ethernet Port
  - Audio Interface:
    - 1-Ch 3.5 mm Audio Interface, Line In
    - 1-Ch 3.5 mm Audio Interface, Mic In
  - Communication Interface:
    - 1 x RS232 In: 8-Pin Small DIN, Maximum Distance: 30 M, Protocols: VISCA/Pelco-D/Pelco-P
    - 1 x RS232 Out: 8-Pin Small DIN, Maximum Distance: 30 M, Protocols: VISCA/Pelco-D/Pelco-P
  - USB Interface: USB 2.0, Type A socket
- USB FEATURES** .....
- Operating Systems: Windows 7 and later
  - Color System: YUY2/MJPEG
  - Video Formats:
    - YUY2 : Max 1080P@30fps
    - MJPEG: Max 2160P@30fps
  - USB audio: Support
  - USB video communication protocol: UVC 1.1
  - USB PTZ Control: Support
  - USB for Local Recording

# UNITE® 260N Pro Camera

- IPC FEATURES** .....
- Video Coding Standard: H.265/H.264/MJPEG
  - Video Stream: First Stream, Second Stream
  - First Stream Resolution: 3840 x 2160, 1920 x 1080, 1280 x 720, 1024 x 576, 960 x 540, 640 x 480, 640 x 360
  - Second Stream Resolution: 640 x 360, 480 x 270, 320 x 240, 320 x 180
  - Video Bit Rate: 32 Kbps - 26624 Kbps
  - Rate Control: Variable Bit Rate, Fixed Bit Rate
  - Frame Rate: 50 Hz: 1 fps - 25 fps, 60 Hz: 1 fps - 30 fps
  - Audio Compression Standard: AAC
  - Audio Bit Rate: 96 Kbps, 128 Kbps, 256 Kbps
  - Supporting Protocols: NDI®|HX2, TCP/IP, HTTP, RTSP, RTMP(S), ONVIF, DHCP, NTP and Multicast
- GENERIC SPECIFICATIONS** .....
- Input Voltage: 48 V PoE (802.3 af)/DC 12 V
  - Input Current: 12 V 1.0 A(Max)
  - Operating Temperature: -10 °c - 40 °c (14 °F - 104°F)
  - Storage Temperature: -40 °c - 60 °c (-40 °F - 140 °F)
  - Power Consumption: 12 W (Max)
  - Mean time between failures: >30000 hours
  - Dimension: 9.4 x 5.6 x 6.3 " (240x 144 x 160 mm)
  - Weight: 2.1 kgs (4.6 lb)
- OPTIONAL ACCESSORIES** .....
- 910-2100-103: Wall Mount for UNITE 200 Camera
  - 910-2100-203: Ceiling Mount for UNITE 200 Camera
  - 910-2100-002: USB 3.0 Cable
- PART NUMBER** .....
- 910-2100-018-N



Scan this Code,  
to learn more

NDI® is a trademark of NDI AB.

ClearOne owns all rights to its logos and trademarks used in connection with this datasheet. All other logos and trademarks appearing on the datasheet are the property of their respective owners. Use of third-party logos or trademarks is for the sole informational purpose of identifying the referenced goods and/or services. Use of a third-party logo or trademark does not necessarily indicate an endorsement by the owner of that mark or a partnership, affiliation, or sponsorship between the owner and ClearOne.

In a time of rapid change, it is difficult to ensure that all information on this datasheet is accurate and up-to-date. The content on this datasheet is for informational purposes only and is subject to change without notice.

## SALES AND INQUIRIES

### Headquarters

5225 Wiley Post Way  
Suite 500  
Salt Lake City, UT 84116

### US & Canada

Tel: +1.801.975.7200

### International

Tel: +1.801.975.7200

### Sales

Tel: +1.801.975.7200  
sales@clearone.com

### Tech Support

Tel: +1.801.974.3760  
videotechsupport@clearone.com